



HAWK

Reach Beyond, with HAWK.

VISIT SITE NOW »



Hitachi EX120 Excavator

VISIT SITE NOW »

www.hawkexcavator.com

| (619) 335 8822

| info@hawkexcavator.com



[VISIT SITE NOW >>](#)

Hitachi EX120 Excavator

The HITACHI EX120 Excavator is a powerful and versatile piece of heavy machinery that is widely used in a variety of construction and industrial applications. This excavator is designed for maximum efficiency and productivity, and is able to handle a wide range of digging and excavation tasks with ease.

One of the key features of the HITACHI EX120 Excavator is its advanced hydraulic system. This system provides precise control over the excavator's movements, allowing for smooth and efficient digging and excavation. The excavator is also equipped with a variety of attachments, such as buckets and hammers, that can be easily swapped out depending on the task at hand.

The HITACHI EX120 Excavator is also designed for maximum safety and operator comfort. The cab of the excavator is spacious and well-ventilated, and is equipped with a variety of controls and displays that make it easy for the operator to monitor and control the excavator's movements. Additionally, the excavator is equipped with a variety of safety features, such as a seatbelt and emergency shut-off switches, to protect the operator in the event of an accident.

The HITACHI EX120 Excavator is a powerful and versatile piece of heavy machinery that is well-suited for a wide range of construction and industrial applications. Its advanced hydraulic system, variety of attachments, and focus on operator safety and comfort make it a popular choice among construction companies and contractors. Additionally, its durability and reliability make it a cost-effective option for long-term use.

PRODUCT FEATURES

Boom / Stick Excavator Option 1

Max Cutting Height	27.4 ft (8 m)
Max Digging Depth	17 ft (5 m)
Max Loading Height	19.5 ft (6 m)
Max Reach Along Ground	25.5 ft (8 m)
Max Vertical Wall Digging Depth	15.3 ft (5 m)
Shipping Height of Unit	9 ft (3 m)
Shipping Length of Unit	24.9 ft (7 m)

[VISIT SITE NOW >>](#)



[VISIT SITE NOW >>](#)

Boom / Stick Excavator Option 2

Max Cutting Height	28.1 ft (9 m)
Max Digging Depth	18.3 ft (5 m)
Max Loading Height	20.2 ft (6 m)
Max Reach Along Ground	26.8 ft (8 m)
Max Vertical Wall Digging Depth	16.5 ft (5 m)
Shipping Height of Unit	9 ft (3 m)
Shipping Length of Unit	24.9 ft (7 m)

Boom / Stick Excavator Option 3

Max Cutting Height	29.2 ft (9 m)
Max Digging Depth	19.9 ft (6 m)
Max Loading Height	21.3 ft (6 m)
Max Reach Along Ground	28.3 ft (9 m)
Max Vertical Wall Digging Depth	18 ft (5 m)
Shipping Height of Unit	9 ft (3 m)
Shipping Length of Unit	25 ft (8 m)

Bucket

Maximum Bucket Capacity	0.9 cu yds (0 m)
Minimum Bucket Capacity	0.3 cu yds (0 m)
Reference Bucket Capacity	0.4 cu yds (0 m)

Dimensions

Ground Clearance	1.5 ft (0 m)
Height – Top of Cab	9 ft (3 m)

[VISIT SITE NOW >>](#)



HAWK

Reach Beyond, with HAWK.

[VISIT SITE NOW >>](#)

Length of Track on Ground	9.5 ft (3 m)
Removal Counterweight Clearance	3 ft (1 m)
Tail Swing Radius	7 ft (2 m)
Width to Outside of Tracks	8.2 ft (2 m)

Engine

Aspiration	Turbocharged
Displacement	264 cu in (0 m)
Engine Model	A-4BG1T
Max Torque	231.6 lbs / ft
Net Power	81 Hp (60 kW)
Power Measured @	2100 rpm
Torque Measured @	1600 rpm

Operating Specifications

Cooling System Fluid Capacity	4.9 gal (15 L)
Engine Oil Capacity	4.3 gal (15 L)
Fuel Capacity	66.1 gal (250 L)
Hydraulic Pump Flow Capacity	50.2 gal / min (189 L / min)
Hydraulic System Fluid Capacity	35.4 gal (132 L)
Hydraulic System Relief Valve Pressure	4980 psi
Operating Weight	26000 lbs (11794 kg)
Swing Drive Fluid Capacity	0.9 gal (0 L)

Swing Mechanism

Swing Speed	12.7 rpm
-------------	----------

[VISIT SITE NOW >>](#)



HAWK

Reach Beyond, with HAWK.

[VISIT SITE NOW >>](#)

Undercarriage

Ground Pressure	5.4 psi
Max Travel Speed	3.5 mph (5 kph)
Number of Carrier Rollers per Side	1
Number of Shoes per Side	44
Number of Track Rollers per Side	7
Shoe Size	19.7 in (48 cm)
Track Gauge	6.6 ft (2 m)

[VISIT SITE NOW >>](#)